



Specifications

Piccolo 18

06-02-2025

ARTICLE NUMBERS

49008055

Piccolo 18 - Adjustable, 120/240 VAC | 60 Hz

49008056

Piccolo 18 - Ungrounded, 120/240 VAC | 60 Hz

MAIN SPECIFICATIONS

Intermittent Power kW at 25°C (77°F)	15 kW
Continuous Power kVA at 25°C (77°F)	18 kVA
Nominal voltage / frequency	Split phase 120/240 VAC 60 Hz
Noise level	57 dB(A) at 7 m, 73 dB(A) at 1 m
Rpm range	2000 .. 2600 rpm, adjustable
Alternator technology	Permanent Magnet
Generator cooling	Indirect water-cooling (engine + alternator)
Generator control	DDC
Control panel	DDC Local
Inverter module	PMG frame 3 (Split phase)
Phase/wire	Split phase, 4 wires
Peak power 2 s	200%
Harmonic distortion	
Frequency tolerance	+/- 0,1%

DIESEL ENGINE SPECIFICATIONS

Engine	WhisperPower Kubota V1505
Engine family	PKBXL01.5DCB
Emission class	Stage V certified / EPA / Tier 4
Displacement	1489 cc
Cylinders	4
Bore & stroke, m (in.)	78 x 78.4 (3.1 x 3.1)
Compression ratio	24.0
Air consumption	
Cooling system	Heat exchanger
Fuel consumption (no load - full load)	4.2-5.6 l/hr
Starter battery charge method/ current	Alternator 12 V / 40 A

DIMENSIONS & WEIGHT

Length x width x height (cabinet), mm (in.)	990 x 560 x 705 (39 x 22 x 27.8)
Length x width x depth (PMG), mm (in.)	567 x 347 x 211 (22.3 x 13.7 x 8.3)
Dry weight cabinet, kg (lb.)	230 (507.1)
Dry weight (PMG), kg (lb.)	30 (66.1)
Exhaust type, mm (in.)	Ø 50 mm, wet (1.6)
Max. operating angle	25° in all directions

OPTIONAL

Optional	2nd start/stop panel, Touch panel 7"
Optional	Ungrounded
Optional	Keel Cooling