



Specifications Piccolo 6

06-02-2025

ARTICLE NUMBER

49004055

Piccolo 6 - Adjustable, 120 VAC | 60 Hz

49004056

Piccolo 6 - Ungrounded, 120 VAC | 60 Hz

MAIN SPECIFICATIONS

Intermittent power kW at 25°C (77°F)	6 kW
Continuous power kVA at 25°C (77°F)	6 KVA
Phase / Nominal voltage / Frequency	1 Phase 120 VAC 60 Hz
Noise level	51 dB(A) at 7 m, 60 dB(A) at 1 m
Rpm range	2400 - 3000 rpm, adjustable
Alternator technology	Permanent magnet
Generator cooling	Indirect water-cooling (engine + alternator)
Generator control	PMG
Inverter module	PMG frame 2
Control panel	PMG + PMG Remote
Phase / Wire	1 Phase, 3 wires
Peak power 2 s	200%
Harmonic distortion	
Frequency tolerance	+/- 0,1%

DIESEL ENGINE SPECIFICATIONS

Engine	WhisperPower Kubota Z482-C
Engine family	NKBXL.719KCB
Emission class	Stage V certified / EPA / Tier 4
Displacement	479cc
Cylinders	2
Bore & stroke mm (in)	67 x 68 (2.6 x 2.7)
Compression ratio	23.5
Air consumption	
Cooling system	Heat exchanger
Fuel consumption (no load - full load)	275 g/kWh
Starter battery charge method/ current	Alternator 12 V / 12.5 A

DIMENSIONS & WEIGHT

Length x width x height (cabinet) mm (in)	530 x 500 x 545 (20.9 x 19.7 x 21.5)
Length x width x depth (PMG) mm (in)	490 x 198 x 191 (19.3 x 7.8 x 7.5)
Dry weight (cabinet) kg (lb)	113 (249.1)
Dry weight (PMG) kg (lb)	9.9 (21.8)
Diameter wet exhaust mm (in)	Ø 40 (1.6)
Max. operating angle	25° in all directions

OPTIONAL

Optional	2nd start/stop panel, Touch panel 7"
Optional	Ungrounded
Optional	Keel Cooling