



Specifications

Piccolo 8

06-02-2025

ARTICLE NUMBER

49005055

Piccolo 8 - Adjustable, 120 VAC | 60 Hz

49005056

Piccolo 8 - Ungrounded, 120 VAC | 60 Hz

MAIN SPECIFICATIONS

Intermittent Power kW at 25°C (77°F)	6 kW
Continuous Power kVA at 25°C (77°F)	6 KVA
Nominal voltage / frequency	1 Phase 120 VAC 60 Hz
Inverter Module	PMG frame 2
Noise level	51 dB(A) at 7 m, 60 dB(A) at 1m
Rpm range	2400 .. 2800 rpm, adjustable
Alternator technology	Permanent magnet
Generator cooling	Indirect water-cooling (engine + alternator)
Generator control	DDC
Control panel	DDC Local + DDC Remote
Phase/wire	1 Phase, 3 wires
Peak power 2 s	200%
Harmonic distortion	
Frequency tolerance	+/- 0,1%

DIESEL ENGINE SPECIFICATIONS

Engine	WhisperPower Kubota Z482
Engine family	NKBXL.719KCB
Emission class	Stage V certified / EPA / Tier 4
Displacement	479 cc
Cylinders	2
Bore & stroke, mm (in.)	67 x 68 (2.6 x 2.7)
Compression ratio	23.5
Air consumption	
Cooling system	Heat exchanger
Fuel consumption (no load - full load)	275 g/kWh
Starter battery charge method/ current	Alternator 12 V / 12.5 A

DIMENSIONS & WEIGHT

Length x width x height (cabinet), mm (in.)	660 x 550 x 622 (26 x 21.7 x 24.5)
Length x width x depth (PMG), mm (in.)	490 x 198 x 191 (19.3 x 7.8 x 7.5)
Dry weight (cabinet), kg (lb.)	154 (339.5)
Dry weight (PMG), kg (lb.)	9.9 (21.8)
Exhaust type, mm (in.)	Ø 40 mm, wet (1.6)
Max. operating angle	25° in all directions

OPTIONAL

Optional	2nd start/stop panel, Touch panel 7"
Optional	Ungrounded
Optional	Keel Cooling